




TACRIP P-D

Single PU rib for indoor areas (DIN)



ACCESSORIES

Templates for standard installation of the single ribs are available as accessories.

PROPERTIES

Self adhesive.

Adhesive: 3M.

For indoor areas on all floors except carpet.

Rib height: 3.3 mm

Rib length: 295 mm

Rib width: 16 mm

Rib surface: chequered

Slip resistance class: R10

MATERIAL

Polyurethane

PROCESSING

1. The substrate must be cleaned. Any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other residues that could impair adhesion must be completely removed.
2. Mark the area where the film is to be placed.
3. Stick the template in the desired position on the floor.
4. We recommend using two connected templates (tongue and groove) at the start.
5. Remove the protective film from the back of the stud and stick it to the desired position using the template.
6. Continue with further studs as described in point 5 until the template is completely filled.
7. Press the studs down further by carefully walking over them with your feet.
8. Remove the template and press the nubs again by carefully walking over them with your feet.
9. If necessary, continue with step 3.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com

DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

The recognised standards and regulations of technology must be observed. Previous data sheets are invalid.

www.dural.com



must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Polyurethane]
Surface	[smooth], [chequered]
Colour	white, black, grey
Length	29.5 cm
Height	3.3 mm
Width mm	16 mm

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
TRPG 1633-3 B	3.3 mm	chequered	black	29.5 cm
TRPG 1633-3 K	3.3 mm	chequered	black	29.5 cm
TRPG 1633-3 SK	3.3 mm	chequered	black	29.5 cm
TRPG 1638-3 B	3.3 mm	chequered	grey	29.5 cm
TRPG 1638-3 K	3.3 mm	chequered	grey	29.5 cm
TRPG 1638-3 SK	3.3 mm	chequered	grey	29.5 cm
TRPG 1630-3 B	3.3 mm	chequered	white	29.5 cm
TRPG 1630-3 K	3.3 mm	chequered	white	29.5 cm
TRPG 1630-3 SK	3.3 mm	chequered	white	29.5 cm
TRP 1633-3 B	3.3 mm	smooth	black	29.5 cm
TRP 1633-3 K	3.3 mm	smooth	black	29.5 cm
TRP 1633-3 SK	3.3 mm	smooth	black	29.5 cm
TRP 1638-3 B	3.3 mm	smooth	grey	29.5 cm
TRP 1638-3 K	3.3 mm	smooth	grey	29.5 cm
TRP 1638-3 SK	3.3 mm	smooth	grey	29.5 cm
TRP 1630-3 B	3.3 mm	smooth	white	29.5 cm
TRP 1630-3 K	3.3 mm	smooth	white	29.5 cm
TRP 1630-3 SK	3.3 mm	smooth	white	29.5 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.