
TACRIP RF-D

Pre-assembled single ribs on a backing sheet for the easy installation of tactile guide strips in accordance with the German standard



TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[TPU]
Surface	[chequered]
Colour	white, black, grey
Length	29.5 cm
Height	3.5 mm
Width mm	16.5 mm
dimension	30 x 15 cm (Folie)

PRODUCT VARIANTS

Ident	Height	Surface	Colour	Length
TRPM 1633-3 SK/12	3.5 mm	chequered	black	29.5 cm
TRPM 1638-3 SK/12	3.5 mm	chequered	grey	29.5 cm
TRPM 1630-3 SK/12	3.5 mm	chequered	white	29.5 cm

Data sheet Accessories

Self adhesive.
For indoor areas on all floors except carpet.

Rib height: 3.5 mm
Rib length: 295 mm
Rib width: 16.5 mm
Slip resistance class: R9

Quick installation

PROPERTIES

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

Self adhesive.
For indoor areas on all floors except carpet.

Rib height: 3.5 mm
Rib length: 295 mm
Rib width: 16.5 mm
Slip resistance class: R9

Quick installation

MATERIAL

TPU (thermoPlastic Polyurethane)

PROCESSING

1. The substrate must be cleaned. Any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other residues that could impair adhesion must be completely removed.
2. Mark the area where the film is to be placed.
3. Remove the protective film from the back of the fixing film. Align the fixing film and stick it in the desired position.
4. Repeat this procedure with additional films until the marked area is completely covered.
5. Press the ribs additionally by carefully running over them with your feet.
6. Remove the fixing film.
7. Press down the ribs again by carefully running over them with your feet.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.