



TI-SHELF LINE

Pentagonal Corner Shelf With Railing And Hanger



MATERIAL

Aluminium can be used wherever medium mechanical stress is expected. Contact with alkaline materials (e.g. tile adhesive) can cause discolouration, which is difficult to remove afterwards. High humidity during the drying phase can intensify this process. Always wipe tile adhesive or grout from visible surfaces immediately with plenty of water, then wipe dry and ensure good room ventilation.

Stainless steel V2A/304 is particularly suitable for applications subject to high mechanical stress and for applications with particularly high requirements for cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid should be avoided. Even with stainless steel, flash rust may occur depending on the environmental conditions and should be removed immediately.

The suitability for mechanical and chemical stress must always be checked in each individual case.

CARE

Aluminium does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry. Avoid using acidic and abrasive cleaning agents.

Stainless steel (304) does not require any special care. If necessary, it can be cleaned with clear, clean water and a few drops of washing-up liquid. Then wipe dry. Avoid using acidic or abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

1. Hold TI-SHELF in the appropriate position on the wall and mark the areas to be cleared in the joints.
2. For subsequent installation, very carefully scrape/remove the marked areas of the joints to a sufficient depth using a suitable tool (knife/multi-tool).

For installation during or after tile laying, thoroughly scrape out the joints at the marked locations with a scraper.

3. Fill the scraped joints with MS polymer adhesive (e.g. Dural Classic Flex 310) and place TI-SHELF.

For installation during or after tile laying, carry out this process after the tiles have dried and the silicone joints have been applied.

4. Seal the wall connection with silicon.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



Protect visible surfaces from contact with tile adhesive or joint mortar and clean immediately with a cloth and clear water if necessary. Then rub dry.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Aluminium], [Stainless Steel (304)]
Surface	[tactile coated], [brushed]
Colour	black, natural, white matt (RAL 9003), sand (RAL 0808005)
Strength mm	1.25, 2
dimension	20 x 20 x 9,5 x 14,5 x 9,5 cm

PRODUCT VARIANTS

Ident	Surface	Colour
TSE LM2+	brushed	natural
TSAC11 LM2+	tactile coated	black
TSAC65 LM2+	tactile coated	sand (RAL 0808005)
TSAC80 LM2+	tactile coated	sand (RAL 0808005)
TSAC12 LM2+	tactile coated	white matt (RAL 9003)

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.