



TACRIP EM-F

Tactile ribs for creating tactile guidance strips according to the French standard



PROPERTIES

For drilling or adhesive fixing.

For indoor (TTLE) and outdoor areas (TTLT E) on all floors except carpet.

Complies with: NF P98-352

Rib height: 5 mm

Rib length: 280 mm

Rib width: 35 mm

Fin surface: corrugated

Slip resistance class: R10

MATERIAL

Stainless steel V2A/304 is particularly suitable for applications subject to high mechanical stress and for particularly high requirements in terms of cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid must be avoided.

No tools made of unalloyed steel may be used during processing. Open cut edges are not rust-resistant. If necessary, separate rust protection must be applied there.

Even with stainless steel, flash rust is possible depending on the environmental conditions and should be removed immediately.

The suitability of the material with regard to mechanical and chemical resistance must always be checked in individual cases.

The suitability for use in terms of mechanical and chemical resistance must always be checked on a case-by-case basis.

CARE

Stainless steel (304) does not require any special maintenance. If necessary, it can be cleaned simply with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.

DURAL GmbH | Südring 11 | D-56412 Ruppach-Goldhausen | Germany | +49 2602/9261-0 | info@dural.com

DURAL Ltd. | Unit 6a | Wakefield Business Centre Denby Dale Rd | Wakefield | WF2 7AZ | United Kingdom | ukinfo@dural.com

The recognised standards and regulations of technology must be observed. Previous data sheets are invalid.

www.dural.com



PROCESSING

1. For the adhesive version, the substrate must be cleaned. Any contaminants such as release agents, preservatives, grease, oil, dust, water, old adhesives/sealants and other residues that could impair adhesion must be completely removed. Mark the area where the ribs are to be placed.

2. Adhesive installation:

2a. Apply MS polymer adhesive (e.g. Speed-Flex) to the back of the rib.

2b. Stick the rib in the desired position.

2c. Repeat steps 2a and 2b with additional ribs until the entire surface has been covered.

2d. At the end of the installation (or in between for large areas), press the ribs down carefully with your feet.

3. Drilling installation:

3a. Place the rib in the desired position.

3b. Hold the rib at a slight angle to mark the drill holes on the floor.

3c. Drill holes approx. 20 mm deep (use a 10 mm drill bit) and carefully remove the drill dust.

3d. Apply a little MS polymer adhesive (e.g. Speed-Flex) to the holes and tap the ribs into place with a rubber mallet.

The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Stainless Steel (304)]
Length	28 cm
Height	5 mm
Width mm	35 mm

PRODUCT VARIANTS

Ident	Height	Length
TTL E 2800 V2A	5 mm	28 cm
TTLT E 2800	5 mm	28 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.