



myVARIO-LINE

Base Set (Without Drain Channel/Design Grating)



ACCESSORIES

1. Drain channel for basic set
2. High-performance horizontal drainage set
3. Vertical drain

PROPERTIES

1. Drain DN 50 with odour trap.
2. EPS mounting block.
3. DURABASE pipe collar ETA-20/0838.
4. Spacers for height adjustment to tile thicknesses of 6-21 mm.
5. Locking/connecting thread for connecting the drain channel to the substructure.
6. Installation height (top edge of screed) only 68 mm.
7. Water seal height 32 mm.
8. Visible dimensions 60 / 70 / 80 / 90 / 100 cm.

MATERIAL

EPS / stainless steel V2A/304 is particularly suitable for applications subject to high mechanical stress and for applications with particularly high requirements for cleanliness, hygiene and chemical resistance. Contact with products containing hydrochloric acid must be avoided.

Even with stainless steel, flash rust may occur depending on the environmental conditions and should be removed immediately.

The suitability for use in terms of mechanical and chemical resistance must always be checked on a case-by-case basis.

CARE

Stainless steel V2A/304 does not require any special care. If necessary, it can be cleaned simply with clear, clean water and a few drops of washing-up liquid. Then wipe dry.

Avoid using acidic, alkaline and abrasive cleaning agents. Flash rust can be removed with commercially available polishes suitable for stainless steel.

PROCESSING

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



1. Determine the height of the finished tile covering.
 2. To do this, include the finished wall surfaces and the planned screed, including a gradient of 2%, for positioning.
 3. Next, include the height of the substrate, including insulation, screed thickness, wall-to-floor connection with joint and the planned tile thickness including mortar bed to calculate the height.
 4. Use the 3 mm and 9 mm spacer plates to set the required height in the sealed base body. This can also be corrected later.
 5. Securely connect the drain channel to the base body and the drain using the screw connection. Use the installation aid to tighten.
 6. Position the base body and adjust it to the required height using tile adhesive. Caution: The channel body must be aligned horizontally and vertically.
 7. Underlay the drain and connect it to the drainage system. Check the system for leaks.
 8. Finish the screed.
 9. For a different installation height, e.g. when laying mosaic or natural stone, the height can be adjusted from 6 to 21. To do this, unscrew the drain channel using the installation aid. Use the required number of suitable spacer plates. Align and position the channel. The distance between the spacer plates and the drain opening should be at least 5 cm on the left and right. Screw the drain channel back on.
 10. Once the screed has dried sufficiently, professionally integrate the pipe collar, which is firmly connected to the shower channel, into the sealing system.
 10. After the screed has dried sufficiently, work the sealing sleeve firmly into the sealing system.
- The generally accepted rules of technology and tiling must be observed. Suitability for use with mechanical and chemical resistance must always be checked in each individual case.

TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[Stainless Steel (304)],[EPS]
Length	60 cm, 70 cm, 80 cm, 90 cm, 100 cm
sight width	600 mm, 700 mm, 800 mm, 900 mm, 1,000 mm
installation height mm	68
visual dimension cm	60, 70, 80, 90, 100

PRODUCT VARIANTS

Ident	Length
VLMB 600	60 cm
VLMB 700/70	70 cm
VLMB 800	80 cm
VLMB 900	90 cm
VLMB 1000	100 cm

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.