



myVARIO-LINE

DIN-Compliant Drain DN 50 Vertical



PROPERTIES

Vertical drain DN50

Water seal height 30 mm

Installation depth 190 mm

Drainage capacity approx. 48 l/min

MATERIAL

PVC is particularly suitable for indoor and outdoor areas with low mechanical stress. The material is dyed throughout and therefore UV-resistant under normal circumstances, but colour differences may occur with constant UV exposure.

The suitability for mechanical and chemical stress must always be checked on a case-by-case basis.

Note: When using coloured joint mortar with ultra-fine colour pigments in combination with plastic profiles, irreversible staining of the profiles may occur. We recommend the use of appropriate protective measures.

CARE

PVC does not require any special care. If necessary, it can be easily cleaned with clear, clean water and a few drops of washing-up liquid.

Solvent-based and abrasive cleaning agents should be avoided.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[PVC]
Colour	blue
installation height mm	190

PRODUCT VARIANTS

Ident	Colour
VLPAS 48	blue

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
 All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
 We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.