



myVARIO-LINE

DIN-Compliant Drain Set DN 50 Horizontal



PROPERTIES

Horizontal drain DN50
2 x EPS mounting blocks, 20 mm each
Water seal height 50 mm
Installation depth 88 mm
Drainage capacity approx. 60 l/min

MATERIAL

PVC is particularly suitable for indoor and outdoor areas with low mechanical stress. The material is dyed throughout and therefore UV-resistant under normal circumstances, but colour differences may occur with constant UV exposure.

The suitability for mechanical and chemical stress must always be checked on a case-by-case basis.

Note: When using coloured joint mortar with ultra-fine colour pigments in combination with plastic profiles, irreversible staining of the profiles may occur. We recommend the use of appropriate protective measures.

CARE

PVC does not require any special care. If necessary, it can be easily cleaned with clear, clean water and a few drops of washing-up liquid.

Solvent-based and abrasive cleaning agents should be avoided.

Please note: For technical reasons, tolerances in color effects of the materials and print are possible. All information is based on the best of our knowledge and belief. No guarantee can be derived from this. We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.



TECHNICAL DIMENSIONS AND PRODUCT VARIANTS

Material	[PVC]
Colour	blue
installation height mm	88

PRODUCT VARIANTS

Ident	Colour
VLPHC 80	blue

Please note: For technical reasons, tolerances in color effects of the materials and print are possible.
All information is based on the best of our knowledge and belief. No guarantee can be derived from this.
We reserve the right to any technical changes if they are in the interest of progress or if they are production-related.