

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only



Tatio

03579 KWWDL34-B30

Tatio Wall Washer Downlight 34w 15° 3000K

- High performance CREE COB LED
- Negligible UV, ideal for retail application



Overview

The Tatio LED Wall Washer

Downlight rotates through 350 degrees and has a 35 degree tilt.

Available in varies CCT and has a high CRI, suitable for retail display, showrooms, entertainment and

hospitality. Made from cast

aluminium with a high-quality

reflector the Kosnic Tatio delivers a

highly efficient, high quality lighting



IP20



General Information

Ambient Temperature Range (°C) -20°C to 50°C

IP Rating IP20

Protection Class II

Rating Internal

Installation Area

Installation Area

Compliance

Others UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	KWWDL34-B30
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	34 W
Driver Code/Part number	CYC036SNL080N
Driver Maximum Power (W)	36 W
Driver Output Current (mA)	800
Power Factor	0.95
Driver Power Factor	≥0.96
Default CCT	3,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Lumens Output Maximum	2,800 lm
Maximum Efficiency	94 lm/W
Emergency Luminous Flux	220 lm
Nominal Lifetime (h)	50,000 h
Weight	1.25Kg
Dimensions (L x W x D) (mm)	159xØ188
Cut-Out (mm)	Ø170mm
Beam Angle - Lumi (°)	15

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Tatio



03579 KWWDL34-B30

Optional Gear

Product Code	Description	Type
EMPAD01	Neka Emergency Downlight kit 2.5W Manual test	Emergency Module

Overview

The Tatio LED Wall Washer

Downlight rotates through 350 degrees and has a 35 degree tilt.

Available in varies CCT and has a high CRI, suitable for retail display, showrooms, entertainment and hospitality. Made from cast aluminium with a high-quality reflector the Kosnic Tatio delivers a highly efficient, high quality lighting




IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class II
Installation Area	Internal



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

