

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only



# Tatio

03582 KWWDL34-S50

## Tatio Wall Washer Downlight 34w 40° 5000K

- High performance CREE COB LED
- Optional add-on emergency kits, available in manual and self-test
- Negligible UV, ideal for retail application



### Overview

The Tatio LED Wall Washer Downlight rotates through 350 degrees and has a 35 degree tilt. Available in varies CCT and has a high CRI, suitable for retail display, showrooms, entertainment and hospitality. Made from cast aluminium with a high-quality reflector the Kosnic Tatio delivers a highly efficient, high quality lighting



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal

### Compliance

Others UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	KWWDL34-S50
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	34 W
Driver Code/Part number	CYC036SNL080N
Driver Maximum Power (W)	36 W
Driver Output Current (mA)	800
Power Factor	0.95
Driver Power Factor	≥0.96
Default CCT	5,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Lumens Output Maximum	2,900 lm
Maximum Efficiency	94 lm/W
Emergency Luminous Flux	220 lm
Nominal Lifetime (h)	50,000 h
Weight	1.25Kg
Dimensions (L x W x D) (mm)	159xØ188
Cut-Out (mm)	Ø170mm
Beam Angle - Lumi (°)	40

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

# Tatio



03582 KWWDL34-S50

## Optional Gear

Product Code	Description	Type
EMPAD01	Neka Emergency Downlight kit 2.5W Manual test	Emergency Module

## Overview

The Tatio LED Wall Washer

Downlight rotates through 350 degrees and has a 35 degree tilt.

Available in varies CCT and has a high CRI, suitable for retail display, showrooms, entertainment and hospitality. Made from cast aluminium with a high-quality reflector the Kosnic Tatio delivers a highly efficient, high quality lighting




IP20



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class II
Installation Area	Internal



Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

