

Tec 2

04731 T5.5-GUF65

Tec 2 5.5W GU10 60° 6500K

- Save energy up to 85%
- Direct replacement of GU10 halogen lamp
- Great dimming compatibility



Overview

The Kosnic Tec 2 range of LED lamps are perfect for home and hospitality settings, with a range of different CCT available. Direct retrofit for standard halogen GU10 lamps and deliver the same aesthetics and ambient light. Perfect for hospitality settings such as restaurants, bars and hotels where ambience is required.



General Information

| | |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 40°C |
| IP Rating | IP20 |
| Protection Rating | Class II |
| Installation Area | Internal |
| L80B10 Lifetime (h) @Ta 25 °C | 12,000 h |

Compliance

| | |
|--------|---|
| LVD | EN 62493:2015+A1:2022, EN 62560:2012+A11:2019 |
| EMC | EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023 |
| Others | UKCA, CE, RoHS, WEEE |

Technical Summary

| | |
|------------------------------------|------------|
| Product Code | T5.5-GUF65 |
| Inrush Current (peak/duration) (A) | 5A/100us |
| Default Power | 5.5 W |
| Power Factor | 0.5 |
| Default CCT | 6,500 K |
| SDCM of CCT | <6 |
| Dimmable | N |
| Flicker | <1% |
| Lumens Output Maximum | 690 lm |
| Maximum Efficiency | 125 lm/W |
| L70B50 Lifetime (h) @Ta 25 °C | 25,000 h |
| L80B10 Lifetime (h) @Ta 25 °C | 12,000 h |
| L90B10 Lifetime (h) @Ta 25 °C | 6,000 h |
| Nominal Lifetime (h) | 25,000 h |
| Glow wire temperature(°C) | 650 |
| Blue Light Hazard | RG1 |
| Weight | 0.046Kg |
| Dimensions (L x W x D) (mm) | 53xØ50 |
| Beam Angle - Lumi (°) | 60 |
| LS Energy Efficiency Class | E |

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

Tec 2


04731 T5.5-GUF65

Overview


The Kosnic Tec 2 range of LED lamps are perfect for home and hospitality settings, with a range of different CCT available. Direct retrofit for standard halogen GU10 lamps and deliver the same aesthetics and ambient light. Perfect for hospitality settings such as restaurants, bars and hotels where ambience is required.



IP20



TEC5.5/GU10
TEC5.5DIM/GU10



GU10Φ51(IEC 60357)

General Information

| | |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 40°C |
| IP Rating | IP20 |
| Nominal Lifetime (h) | 25,000 h |
| Protection Rating | Class II |
| Installation Area | Internal |

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

