

# Ventas 2

05723 VEN10-SCT/S



## Ventas 2 IP65 floodlight 10W CCT switch w/remote PIR ON/OFF

- CCT switching with remote control included
- Surge protection
- Diecast aluminium body
- Slim profile
- 1m of H05RN-F 3 x 1mm<sup>2</sup> cable

### Overview

Kosnic Ventas LED floodlights with PIR sensor option. Available in 10W, 20W, 30W and 50W with switchable CCT by remote control (included).

The high-quality aluminium floodlights make ideal replacements for energy-hungry halogen lighting and are suitable for outdoor use offering high lumen efficiency and a long life



**IP65**



### General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IK Rating	IK04
IP Rating	IP65
Protection Rating	Class I
Installation Area	External
L80B10 Lifetime (h) @Ta 25 °C	36,000 h

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-5:2015, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	VEN10-SCT/S
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	0.06A/60µs
Default Power	10 W
Power Factor	0.75
Settable Colour Temperatures	3000K, 4000K, 6500K
CRI	≥82
Dimmable	Specific Dimmer
Lumens Output Maximum	660 lm
Maximum Efficiency	66 lm/W
L70B50 Lifetime (h) @ Ta 25 °C	36,000 h
L80B10 Lifetime (h) @ Ta 25 °C	36,000 h
L90B10 Lifetime (h) @ Ta 25 °C	25,000 h
Nominal Lifetime (h)	30,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.39Kg
Dimensions (L x W x D) (mm)	101x166x56
Beam Angle - Lumi (°)	105
LS Energy Efficiency Class	F

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

# Ventas 2

05723 VEN10-SCT/S

## Accessories

Product Code	Description	Type
KCWP3IN	IP67 in-line connector	Connector kit
<b>Settable (Default in Bold)</b>	<b>Variable</b>	
<b>Rated Power (W)</b>	<b>CCT (K)</b>	<b>Total Luminous Flux (lm)</b>
10	3000	590
<b>10</b>	<b>4000</b>	<b>660</b>
10	6500	590

## Overview



Kosnic Ventas LED floodlights with PIR sensor option. Available in 10W, 20W, 30W and 50W with switchable CCT by remote control (included).

The high-quality aluminium floodlights make ideal replacements for energy-hungry halogen lighting and are suitable for outdoor use offering high lumen efficiency and a long life



## General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IK Rating	IK04
IP Rating	IP65
Nominal Lifetime (h)	30,000 h
Protection Rating	Class I
Installation Area	External



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

