

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

Milo

Kosnic


06513 MIL5F36-W40

## Milo, Edge-lit batten, watt switching, 27/36W, 5ft 4000K

- Designed to replace the popular twin T8 surface modular
- Flicker-free driver as standard
- DALI, 1-10V (0-10V) and PUSH alternative driver available
- Plug & play emergency module
- BESA box fitting points

### Overview

The Kosnic Milo LED battens are replacements for standard ceiling battens. These advanced battens are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light to maintain well-being.



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP20
Protection Rating	Class III
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	50,000 h

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	MIL5F36-W40
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	30A/110µs
Default Power	36 W
Driver Code/Part number	Philips CertaDrive 36W 0.9A 40V 230V I
Driver Maximum Power (W)	36 W
Driver Output Current (mA)	900
Power Factor	>0.94
Driver Power Factor	0.9
Default CCT	4,000 K
SDCM of CCT	<6
CRI	≥82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	4,000 lm
Maximum Efficiency	111 lm/W
Emergency Luminous Flux	480 lm
L70B50 Lifetime (h) @ Ta 25 °C	60,000 h
L80B10 Lifetime (h) @ Ta 25 °C	50,000 h
L90B10 Lifetime (h) @ Ta 25 °C	40,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	850
Blue Light Hazard	RG1
Weight	6.3Kg
Dimensions (L x W x D) (mm)	1555x310x50
LS Energy Efficiency Class	E

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

**7** Years  
Product Warranty  
UK Only

**2** Years  
On-Site Warranty  
Main-land UK Only

Milo

Kosnic 

06513 MIL5F36-W40

## Overview

The Kosnic Milo LED battens are replacements for standard ceiling battens. These advanced battens are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light to maintain well-being.



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class III
Installation Area	Internal

## Optional Gear

Product Code	Description	Type
UEM04/ST	Universal Emergency Module Pro 4W Self Test	Self-test Emergency Module
UEM04	Universal Emergency Module Pro 4W	Emergency Module
UEM03/ST	Universal Emergency Module 3W Self Test	Self-test Emergency Module
UEM03	Universal Emergency Module 3W	Emergency Module
CYC030TDC30-90	30W DALI2 1-10V primary push dim driver (KL30C-PDiIV)	Dimmable Driver
UEM04/DA	Universal Emergency Module Pro DALI 4W	Emergency Module
DRC30/DA	Dimmable Driver: 30W DALI, 1-10V, Primary PUSH Driver	Dimmable Driver

## Accessories

Product Code	Description	Type
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS04	LED Panel & Slim Line 2 suspension kit (4 cables per bag)	Suspension Kit
SUS04/25	Suspension kit 2.5m Alden & Nevis & Slim Line 2 (4 cables per bag)	Suspension Kit



Product Code	Length (mm)	Width (mm)	Height (mm)	Fixing (mm)
4F	1255	310	50	800
5F	1555	310	50	800

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK