

WiZ Pro GU10

06778 WIZ50/GU10-TW

WiZ Pro 4.7W (=50W) GU10 927-65 TW

- High efficiency of up to 85lm/W
- Easily controlled via smart device with Internet connection
- Dimmable tuneable
- Control lights seamlessly with WiZ app
- 2200-6500K CCT (RGB + TW) / 2700-6500K CCT (TW)
- Retrofit replacement for halogen GU10 lamps

Overview

The WiZ Pro product can be easily controlled via a smart device with an internet connection. Define schedules to turn the lights on and off according to a routine, set scenes and light modes, all to accommodate the needs of your project, and control the lights seamlessly with WiZ app.



General Information

Ambient Temperature Range (°C)	-20°C to 45°C
Installation Area	Internal

Compliance

Others	UKCA, CE, RoHS, WEEE
--------	----------------------



Technical Summary

Product Code	WIZ50/GU10-TW
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	N/A
Default Power	4.7 W
Power Factor	0.51
Settable Colour Temperatures	2200K-6500K (TW)
CRI	90
Dimmable	Y
Lumens Output Maximum	400 lm
Maximum Efficiency	85 lm/W
L70B50 Lifetime (h) @ Ta 25 °C	15,000 h
Nominal Lifetime (h)	15,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.05Kg
Dimensions (L x W x D) (mm)	58xØ50
LS Energy Efficiency Class	F

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com




Kosnic Lighting KosnicUK KosnicLightingUK

WiZ Pro GU10

06778 WIZ50/GU10-TW

Overview

The WiZ Pro product can be easily controlled via a smart device with an internet connection. Define schedules to turn the lights on and off according to a routine, set scenes and light modes, all to accommodate the needs of your project, and control the lights seamlessly with WiZ app.



General Information

Ambient Temperature Range (°C)	-20°C to 45°C
Nominal Lifetime (h)	15,000 h
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

