

# Epping

07097 EPP03VER-BLK

## Epping, Vertical LED brick light, 3W, 22°, 4000K, Black

- Die-cast aluminium body with polycarbonate front cover
- Choice of styles and mounting positions
- Polycarbonate back box for easy installation
- Black and dark grey textured powder coat finishing



### Overview

The Epping LED brick lights are available in versions suitable for ground or wall mounting. Wall mounting horizontal (standard) or vertical. Made from die-cast aluminium with a polycarbonate diffuser the weather resistant brick lights are suited for outdoor areas such as driveways and car parks. Available in black or grey finish.



**IP65**



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	54,000 h

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	EPP03VER-BLK
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	16A / 100µs
Default Power	3 W
Power Factor	0.5
Default CCT	4,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	5%
Lumens Output Maximum	140 lm
Maximum Efficiency	47 lm/W
L70B50 Lifetime (h) @Ta 25 °C	54,000 h
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
L90B10 Lifetime (h) @Ta 25 °C	27,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.9Kg
Dimensions (L x W x D) (mm)	232x78.5x116
Beam Angle - Lumi (°)	22
LS Energy Efficiency Class	E

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)




Kosnic Lighting KosnicUK KosnicLightingUK

# Epping

07097 EPP03VER-BLK

## Overview

The Epping LED brick lights are available in versions suitable for ground or wall mounting. Wall mounting horizontal (standard) or vertical. Made from die-cast aluminium with a polycarbonate diffuser the weather resistant brick lights are suited for outdoor areas such as driveways and carparks. Available in black or grey finish.



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

