

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only




Kaz II

07221 KAZ12-SCT

Kaz II, LED wall pack, 12W IP65 CCT switchable, dusk to dawn

- Anti-corrosion polycarbonate body
- IP65
- Durable and rugged IK08 polycarbonate construction
- Dusk to dawn sensor by default and rewirable
- BESA box fitting points



Overview

The Kaz II with an updated elegant design and improved dusk dawn sensor. Its durable construction IK08 and IP65 ratings makes it perfect for using in demanding environments as it can be cleaned with a pressure washer. CCT switchable, ability to disable the integrated dusk dawn sensor, and emergency options provides plenty of flexibility.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	50,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023

Technical Summary

Product Code	KAZ12-SCT
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	14A/360µs
Default Power	12 W
Power Factor	>0.94
Default CCT	4,000 K
Settable Colour Temperatures	3000k, 4000k, 6500k
SDCM of CCT	<6
CRI	≥82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	1,600 lm
Maximum Efficiency	134 lm/W
Emergency Luminous Flux	160 lm
L70B50 Lifetime (h) @Ta 25 °C	50,000 h
L80B10 Lifetime (h) @Ta 25 °C	50,000 h
L90B10 Lifetime (h) @Ta 25 °C	34,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.76Kg
Dimensions (L x W x D) (mm)	218.5x147.5x79

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Kaz II



07221 KAZ12-SCT

Optional Gear

Product Code	Description	Type
EMDD02/ST	2W self-test emergency module for LED DD and bulkhead	Self-test Emergency Module
EMDD02	2W standard emergency module for LED DD and bulkhead	Emergency Module

Settable (Default in Bold)		Variable
Rated Power (W)	CCT (K)	Total Luminous Flux (lm)
12	3000	1500
12	4000	1600
12	6500	1500

Overview

The Kaz II with an updated elegant design and improved dusk dawn sensor. Its durable construction IK08 and IP65 ratings makes it perfect for using in demanding environments as it can be cleaned with a pressure washer. CCT switchable, ability to disable the integrated dusk dawn sensor, and emergency options provides plenty of flexibility.




IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK