



## Overview

The Universal Emergency Module (UEM) with available Automatic Self-Test (AST) version is suitable for class III luminaires with integrated LEDs and separate LED drivers. Provides an operation time of three hours. The UEM can be installed within a luminaire or within the ceiling void.







## General Information

IP Rating	IP20
Protection	Class II
Rating	
Installation	Internal
Area	





07239 UEM04/DA

# 4W DALI Universal Emergency Module Pro

- Built-in loop-in and loop-out terminals
- DALI-2 conforming to EN 62386-202
- Built-in cable clamp with push to release function
- Designed to use with all LED luminaires (Class III) with external driver
- Easy plug & play installation
- For maintained or non-maintained emergency lighting systems
- Internal Li-ion battery with improved lifespan
- Easy battery replacement





T 1 : 10				
Technical Summary				
Product Code	UEM04/DA			
Weight	0.35Kg			
Dimensions (L x W x D) (mm)	211x91x32			
UEM/EME Battery Life	4 y			
UEM/EME Input Voltage	220-240Vac 50/60Hz			
UEM/EME Ambient Temperature Range	0°C to 45°C			

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

















## Overview

The Universal Emergency Module (UEM) with available Automatic Self-Test (AST) version is suitable for class III luminaires with integrated LEDs and separate LED drivers. Provides an operation time of three hours. The UEM can be installed within a luminaire or within the ceiling void.







# General Information

P Rating	IP20	
Protection	Class II	
Rating		
nstallation	Internal	
Area		

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com











# Kosnic Lighting Kosnic UK Kosnic Lighting UK Kosnic UK

# **UEM Pro DALI**



## 07239 UEM04/DA

# Accessories

Product Code	Description	Туре
BAT26LI2	Li-ion Battery Pack 2600mAh for UEM04/DA	Battery
BAT20LFP2	LPF battery 6.4V 2000mAh for BEM03	Battery
BATS26LI2	Li-ion Battery Pack 2600mAh for UEM04/DA	