

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Inda

Kosnic

07794 IND5F50/DA

Inda Slim backlight batten 5ft 28/50W CCT switch DALI

- Switchable wattage and CCT switchable (3000K/4000K/5000K)
- Emergency options available
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- DALI-2 DT 6, DSI, switchDIM, corridor FUNCTION V2 option available
- 228mm blank section with knock out sections to fit in motion sensor and emergency downlight
- 1-10 (0-10V) dimming
- 20mm conduit entry
- Included 2.0m drop suspension kit

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP20
Protection Rating	Class I
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	60,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE



Technical Summary

Product Code	IND5F50/DA
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	12.08A/188µs
Settable Wattages	28W, 50W
Driver Code/Part number	Boke BK-DAL0x0
Settable Colour Temperatures	3000K, 4000K, 5000K
SDCM of CCT	<6
CRI	≥82
Dimmable	Y
Flicker	<1%
Lumens Output Maximum	5,700 lm
Maximum Efficiency	116 lm/W
L70B50 Lifetime (h) @ Ta 25 °C	60,000 h
L80B10 Lifetime (h) @ Ta 25 °C	60,000 h
L90B10 Lifetime (h) @ Ta 25 °C	48,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	5.9Kg
Dimensions (L x W x D) (mm)	1574x228x37
Conduit Entry 20mm	Yes

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Inda

Kosnic 

07794 IND5F50/DA

Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

Optional Gear

Product Code	Description	Type
MWS-REC/DV	Recessed microwave Sensor, 1-10V dim output, remote required	Microwave Sensor
NTR03/ST	Nitro Emergency Downlight 3W Self-test White	Emergency Light
NTR03	Nitro Emergency Downlight 3W Manual test White	Emergency Light
MWS-SID/DV	M31 Side-Mount 1-10V microwave motion sensor MC054V RC	Microwave Sensor
MWS-SID	M30 Side-mount microwave motion ON/OFF sensor	Microwave Sensor
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
IND-BLANK	Inda interlock blank section 228mm	Connector kit

Settable (Default in Bold)		Variable					
Rated Power (W)	CCT (K)	Maximum Current Draw (mA)	Total Luminous Flux (lm)	Power Factor	LS Energy Consumption in on-mode (kWh/1000H)	LS Energy Efficiency Class	LS Useful Luminous Flux (lm)
28	3000	130	2950	0.94	27	D	4500
28	4000	130	3250	0.94	27	C	4800
28	5000	130	2950	0.94	27	D	4500
50	3000	224	5250	0.97	45	D	7200
50	4000	224	5700	0.97	45	C	7800
50	5000	224	5250	0.97	45	D	7200
Rated Power (W)	CCT (K)	LS On-Mode Power (Pon) (W)	LS Chromaticity Co-Ordinates (X)	LS Chromaticity Co-Ordinates (Y)	LS R9 CRI (LED/OLED)	Light Source Supply	
28	3000	27	0.433	0.4	5	36Vdc 750mA	
28	4000	27	0.383	0.372	10	36Vdc 750mA	
28	5000	27	0.342	0.349	5	36Vdc 750mA	
50	3000	45	0.433	0.4	5	36Vdc 1250mA	
50	4000	45	0.383	0.372	10	36Vdc 1250mA	
50	5000	45	0.342	0.349	5	36Vdc 1250mA	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK


7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Inda

Kosnic 

07794 IND5F50/DA



Overview

The slim backlight Inda batten is CCT switchable and 1-10V/0-10V dimmable. With multiple wattage, DALI dimming, side mounted sensors and integrated emergency options. If you want to keep the slim design on show, multiple fittings can be joined with blank sections which can be fitting with sensors or emergency downlights.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK