

# Aspen

07907 ASPC12-GRY

## Aspen 12W Up and Down Circle LED Wall Light Grey

- Adjustable beam angle, 0-90
- Push-fit terminals for fast and easy wiring
- Two cable entries, loop in and loop out
- Die-cast aluminium body with grey and black finishing options



### Overview

Aspen provides a modern look to any domestic and commercial outdoor lighting requirements. With options of grey or black finishing, adjustable beam angle and switchable CCT to suit different lighting moods.



**IP65**



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK02
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	58,000 h

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	ASPC12-GRY
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	16.9A/2.26us
Default Power	12 W
Power Factor	0.5
Settable Colour Temperatures	3000K, 4000K, 6500K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	698 lm
Maximum Efficiency	58 lm/W
L70B50 Lifetime (h) @Ta 25 °C	91,000 h
L80B10 Lifetime (h) @Ta 25 °C	58,000 h
L90B10 Lifetime (h) @Ta 25 °C	28,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.615Kg
Dimensions (L x W x D) (mm)	135x120x100
Beam Angle - Lumi (°)	0-90
LS Energy Efficiency Class	E

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com




Kosnic Lighting KosnicUK KosnicLightingUK

07907 ASPC12-GRY

## Overview

Aspen provides a modern look to any domestic and commercial outdoor lighting requirements. With options of grey or black finishing, adjustable beam angle and switchable CCT to suit different lighting moods.

Rated Power (W)	CCT (K)	Total Lumen (lm)
12	3000 Warm White	582
12	4000 Cool White	698
12	6500 Day Light	627



**ASPC12**



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK02
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

