

Aspen

07908 ASPC20-BLK

Aspen 20W Up and Down Circle LED Wall Light Black

- Adjustable beam angle, 0-90
- Push-fit terminals for fast and easy wiring
- Two cable entries, loop in and loop out
- Die-cast aluminium body with grey and black finishing options



Overview

Aspen provides a modern look to any domestic and commercial outdoor lighting requirements. With options of grey or black finishing, adjustable beam angle and switchable CCT to suit different lighting moods.



IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK02
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	58,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	ASPC20-BLK
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	24.4A/3.3us
Default Power	20 W
Power Factor	0.5
Settable Colour Temperatures	3000K, 4000K, 6500K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	1,021 lm
Maximum Efficiency	51 lm/W
L70B50 Lifetime (h) @Ta 25 °C	91,000 h
L80B10 Lifetime (h) @Ta 25 °C	58,000 h
L90B10 Lifetime (h) @Ta 25 °C	28,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	1.03Kg
Dimensions (L x W x D) (mm)	168x144x120
Beam Angle - Lumi (°)	0-90
LS Energy Efficiency Class	E

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com




07908 ASPC20-BLK

Overview

Aspen provides a modern look to any domestic and commercial outdoor lighting requirements. With options of grey or black finishing, adjustable beam angle and switchable CCT to suit different lighting moods.

Rated Power (W)	CCT (K)	Total Lumen (lm)
20	3000 Warm White	872
20	4000 Cool White	1021
20	6500 Day Light	956



ASPC20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK02
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

