5 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Nitro Surface 2

Kosnic
LIGHTING • SIMPLY BETTER

07967 NTRSU201-BLK/ST

Nitro Surface 2 Emergency Downlight 1.6W Self-test Black

- Self-test
- Option of standard and self-test models
- Non-maintained Downlight, >3hrs
- Optional self-test model according to BS-EN-62034-2012
- Available in white or black
- Standard and corridor lens included





Overview

The Nitro Surface non-maintained LED emergency lights provide a simple self-contained emergency lighting solution. The emergency lights have internal LiPo4 batteries that will provide power for a three hour duration following a cut in the power supply. Self-test version also available.

IP65

General Information

IP Rating	IP65
Protection Rating	Class II
Installation Area	Internal

Technical Summary	
Product Code	NTRSU201-BLK/ST
Lumens Output Maximum	120 lm
Maximum Efficiency	120 lm/W
Dimensions (L x W x D) (mm)	46x∅156
UEM/EME Battery Life	4 y
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 40°C
UEM/EME CCT	6,500 K
UEM/EME Input Power (Max)	1.6 W
UEM/EME Weight	0.29 kg
Beam Angle - Lumi (°)	170 or 50x160

Compliance

LVD	EN 60598-1:2024, EN 60598-2-22:2022, EN 61347-1:2015+A1:2021, EN 61347-2-7:2012+A1:2021, EN 61347-2-13:2014+A1:2017, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE, REACH

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

Kosnic Lighting KosnicUK KosnicLightingUK

5 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Nitro Surface 2

Kosnic
LIGHTING • SIMPLY BETTER

07967 NTRSU201-BLK/ST

Accessories

Product Code	Description	Type
BAT18LFP1	Battery for Kosnic Emergencies	Battery

Overview

The Nitro Surface non-maintained LED emergency lights provide a simple self-contained emergency lighting solution. The emergency lights have internal LiPo4 batteries that will provide power for a three hour duration following a cut in the power supply. Self-test version also available.



General Information

IP Rating	IP65
Protection Rating	Class II
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK