

Pixley

07990 PIX20-BLK

Pixley 20W Spot twin wall light CCT switchable Black

- CCT switchable
- Optional plug-in remote controlled PIR sensor
- Diecast aluminium body
- IP65 rated with PIR sensor

Overview

The Pixley twin LED security lights with PIR sensor option offers good lighting coverage for domestic and commercial outdoor lighting requirements. With switchable CCT for different ambient requirements.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK07
IP Rating	IP54
Protection Rating	Class I
Installation Area	External

Technical Summary

Product Code	PIX20-BLK
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	20 W
Power Factor	>0.5
Settable Colour Temperatures	3000K, 4000K, 5700K
CRI	82
Lumens Output Maximum	1,700 lm
Maximum Efficiency	85 lm/W
Nominal Lifetime (h)	50,000 h
Dimensions (L x W x D) (mm)	237x164
Beam Angle - Lumi (°)	120

Compliance

LVD	EN 60598-1:2024, EN 60598-2-5:2015, EN 62471:2008, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



07990 PIX20-BLK

Overview

The Pixley twin LED security lights with PIR sensor option offers good lighting coverage for domestic and commercial outdoor lighting requirements. With switchable CCT for different ambient requirements.

Optional Gear

Product Code	Description	Type
DELG-PIR	Della Go PIR Sensor (requires Remote Control, order separately)	PIR Sensor

Accessories

Product Code	Description	Type
RMT-UNI	Universal Remote Control for Kosnic motion sensors	Remote Control

Rated Power (W)	CCT (K)	Total Lumen (lm)
20	3000	1600
20	4000	1700
20	5700	1600



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK07
IP Rating	IP54
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	External

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

