5 Years
Product Warranty
UK Only

Pixley

Kosnic
LIGHTING • SIMPLY BETTER

07991 PIX20-WHT

Pixley 20W Spot twin wall light CCT switchable White

- Switchable CCT (3000/4000/5700K)
- Optional plug-in emergency module
- Die-cast aluminium body
- Optional plug-in PIR ON/OFF sensor compatible with Uni-Remote
- IP54 rated with PIR sensor





Overview

The Pixley twin LED security lights with PIR sensor option offers good lighting coverage for domestic and commercial outdoor lighting requirements. With switchable CCT for different ambient requirements.

IP54

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK07
IP Rating	IP54
Materials	Housing: Die-cast aluminium+Glass
Protection Rating	Class I
Installation Area	External
L80B10 Lifetime (h) @Ta 25 °C	73,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-5:2015, EN 62471:2008, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary	
Product Code	PIX20-WHT
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	20 W
Power Factor	0.5
Settable Colour Temperatures	3000K, 4000K, 5700K
SDCM of CCT	<6
CRI	82
Lumens Output Maximum	1,700 lm
Maximum Efficiency	85 lm/W
L80B10 Lifetime (h) @Ta 25 °C	73,000 h
Nominal Lifetime (h)	50,000 h
Dimensions (L x W x D) (mm)	237x164
Beam Angle - Lumi (°)	120

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

Kosnic Lighting KosnicUK KosnicLightingUK

5 Years
Product Warranty
UK Only

Pixley

Kosnic
LIGHTING • SIMPLY BETTER

07991 PIX20-WHT

Optional Gear

Product Code	Description	Type
DELG-PIR	Della Go PIR Sensor (requires Remote Control, order separately)	PIR Sensor

Accessories

Product Code	Description	Type
RMT-UNI	Universal Remote Control for Kosnic motion sensors	Remote Control

Overview

The Pixley twin LED security lights with PIR sensor option offers good lighting coverage for domestic and commercial outdoor lighting requirements. With switchable CCT for different ambient requirements.






General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK07
IP Rating	IP54
Materials	Housing: Die-cast aluminium+Glass
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	External

Rated Power (W)	CCT (k)	Total Lumen (lm)
20	3000	1600
20	4000	1700
20	5700	1600

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK