7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Echo 3

Kosnic
LIGHTING • SIMPLY BETTER

08049 ECH3200-W50/DA

Echo 3 DALI Circular Highbay 200W 5000K

- High efficiency of 170lm/W
- Diecast aluminium
- Dimmable via a wired 1-10v dimmer switch
- IP65 & vandal resistant (IK10)
- Optional reflectors on all models
- Wattage switching at the side of high bay
- Optional plug-in emergency modules, available in manual, self-test and DALI
- Optional plug-in microwave corridor sensor compatible with Uni-Remote





Overview

The Echo 3 provides a high efficiency of 145lm/W or a range of wattage options and 1-10v dimming for further control. The IP65 rating and range of shades means the Echo III is suited for a range of areas both internal and external, with optional emergency gear if needed.

IP65

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	87,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary	
Product Code	ECH3200-W50/DA
Input Voltage Supply	100-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	100A/300µs
Default Power	200 W
Driver Code/Part number	Sosen
Power Factor	0.98
Default CCT	5,000 K
SDCM of CCT	<6
CRI	≥82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	30,000 lm
Maximum Efficiency	150 lm/W
Emergency Luminous Flux	900 lm
L70B50 Lifetime (h) @Ta 25 °C	138,000 h
L80B10 Lifetime (h) @Ta 25 °C	87,000 h
L90B10 Lifetime (h) @Ta 25 °C	41,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	2.55Kg
Dimensions (L x W x D) (mm)	164x∅298
Beam Angle - Lumi (°)	90
LS Energy Efficiency Class	D

Tel: 01635 523 713
Email: sales@kosnic.com
Kosnic.com
Kosnic Lighting KosnicUK KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Echo 3

Kosnic
LIGHTING • SIMPLY BETTER

08049 ECH3200-W50/DA

Overview

The Echo 3 provides a high efficiency of 145lm/W or a range of wattage options and 1-10v dimming for further control. The IP65 rating and range of shades means the Echo III is suited for a range of areas both internal and external, with optional emergency gear if needed.

IP65

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Optional Gear

Product Code	Description	Type
EMHB08	Emergency Module 8W Manual for Kosnic Highbays	Emergency Module
EMHB08/ST	Emergency Module 8W Self-test for Kosnic Highbays	Self-test Emergency Module
EMHB10	Emergency Module 10W Manual for Kosnic Highbays	Emergency Module
EMHB10/ST	Emergency Module 10W Self-test for Kosnic Highbays	Self-test Emergency Module
EMHB10/DA	Emergency Module 10W DALI for Kosnic Highbays	Emergency Module

Accessories

Product Code	Description	Type
ECH-SHD-AL	Echo aluminium shade for ECHP160, ECHP200, ECH3P200	Shade
ECH-SHD-PC	Echo, PC bell-shaped shade for ECH150, ECH200	Shade
ECH-LID	Echo Translucent bottom enclosure ∅404 x 40 mm for ECH-SHD-PC	Shade

Settable (Default in Bold)		**Variable**			
CCT (K)	**Rated Power (W)**	**Maximum Current Draw (mA)**	**Total Luminous Flux (lm)**	**Power Factor**	**Light Source Supply**
5000	100	460	15000	0.95	195Vdc 480mA
5000	150	690	22500	0.96	195Vdc 720mA
5000	**200**	**890**	**30000**	**0.98**	**195Vdc 920mA**

Tel: 01635 523 713
Email: sales@kosnic.com
Kosnic.com
Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK