

# Vintage Filament GLS

08166 VA4.2-BC25

## Vintage Filament A60 (GLS) 4.2W BC (B22) 2500K gold antique

- Special coating with a gold finish gives an antique appearance
- Linear LED filament provides a traditional appearance
- Creates a warm and cosy living space
- Even light distribution
- Save energy up to 90% compared with an incandescent filament lamp



### Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	15,000 h

### Compliance

LVD	EN 62031:2020, EN 62471:2008, EN 62493:2015+A1:2022, EN 62560:2012+A11:2019
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	VA4.2-BC25
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	3.6A/1440us
Default Power	4.2 W
Power Factor	0.4
Default CCT	2,500 K
SDCM of CCT	<6
CRI	80
Dimmable	N
Flicker	<10%
Lumens Output Maximum	450 lm
Maximum Efficiency	112 lm/W
L70B50 Lifetime (h) @Ta 25 °C	15,000 h
L80B10 Lifetime (h) @Ta 25 °C	15,000 h
L90B10 Lifetime (h) @Ta 25 °C	5,000 h
Nominal Lifetime (h)	15,000 h
Blue Light Hazard	RG1
Weight	0.032Kg
Dimensions (L x W x D) (mm)	104xØ60
LS Energy Efficiency Class	F

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)


[Kosnic.com](http://Kosnic.com)



08166 VA4.2-BC25

## Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IP Rating	IP20
Nominal Lifetime (h)	15,000 h
Protection Rating	Class II
Installation Area	Internal

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

