

Vintage Filament Globe G95 (Dim)

08170 VGM4.2D-BC25

Vintage Filament Medium Globe (G95) 4.2W Dimmable BC (B22)

- Special coating with a gold finish gives an antique appearance
- Linear LED filament provides a traditional appearance
- Creates a warm and cosy living space
- Even light distribution
- Save energy up to 90% compared with an incandescent filament lamp

Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	15,000 h

Compliance

LVD	EN 62031:2020, EN 62471:2008, EN 62493:2015+A1:2022, EN 62560:2012+A11:2019
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	VGM4.2D-BC25
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	3.6A/1440us
Default Power	4.2 W
Power Factor	0.4
Default CCT	2,500 K
SDCM of CCT	<6
CRI	80
Dimmable	Y
Flicker	<10%
Lumens Output Maximum	450 lm
Maximum Efficiency	112 lm/W
L70B50 Lifetime (h) @Ta 25 °C	15,000 h
L80B10 Lifetime (h) @Ta 25 °C	15,000 h
L90B10 Lifetime (h) @Ta 25 °C	5,000 h
Nominal Lifetime (h)	15,000 h
Blue Light Hazard	RG1
Weight	0.057Kg
Dimensions (L x W x D) (mm)	138xØ95
LS Energy Efficiency Class	F

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com




Kosnic Lighting KosnicUK KosnicLightingUK

08170 VGM4.2D-BC25

Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.



General Information

Ambient Temperature Range (°C)	-20°C to 40°C
IP Rating	IP20
Nominal Lifetime (h)	15,000 h
Protection Rating	Class II
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

