

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only


# Avon Pro



08752 AVOP4FT-SCT

## Avon Pro 4ft Twin 20W/26W/32W/36W switchable CCT

- High efficiency up to 170lm/W
- Optional plug-in microwave corridor sensor compatible with Uni-Remote
- Switchable wattage and CCT (3000/4000/6000K)
- Optional plug-in emergency modules, available in standard, self-test and DALI
- T8 non-corrosive LED replacement
- Opal diffuser
- 20mm Conduit entry
- IP65 and vandal resistant (IK08)
- Optional plug-in DALI conversion module



### Overview

The Avon Pro LED non-corrosive battens utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications. The product range is completely customisable and has optional microwave sensor and emergency options and is both wattage and CCT switchable.



IP65



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Materials	Housing: Polycarbonate
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	179,000 h

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

### Technical Summary

Product Code	AVOP4FT-SCT
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	16.5A / 270µs
Settable Wattages	20W, 26W, 32W, 36W
Driver Code/Part number	BK-PYN042E-A0350AYV (BOKE)
Driver Maximum Power (W)	42 W
Driver Output Current (mA)	200/ 250/ 300/ 350
Power Factor	0.90
Driver Power Factor	0.9
Settable Colour Temperatures	3000K, 4000K, 6000K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<2%
Lumens Output Maximum	5,760 lm
Emergency Luminous Flux	350 lm
L70B50 Lifetime (h) @Ta 25 °C	287,000 h
L80B10 Lifetime (h) @Ta 25 °C	179,000 h
L90B10 Lifetime (h) @Ta 25 °C	83,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	850
Blue Light Hazard	RG1
Weight	1.75Kg
Dimensions (L x W x D) (mm)	1265x117x80
Conduit Entry 20mm	Yes
LS Energy Efficiency Class	C

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

**7** Years  
Product Warranty  
UK Only

**2** Years  
On-Site Warranty  
Main-land UK Only

# Avon Pro



08752 AVOP4FT-SCT

## Overview

The Avon Pro LED non-corrosive batters utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications. The product range is completely customisable and has optional microwave sensor and emergency options and is both wattage and CCT switchable.



**IP65**



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Materials	Housing: Polycarbonate
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External


## Optional Gear

Product Code	Description	Type
BEM303	BEM Emergency Module 3W for Kosnic Batters	Emergency Module
BEM303/SST	BEM Duo 3W Manual/Self test emergency module for Kosnic batters	Emergency Module
BEM303/DA	BEM 3W DALI switchable for Kosnic Batters	Emergency Module
SOV-M/D	Sova Plug-in microwave motion and daylight sensor	Microwave Sensor

## Accessories

Product Code	Description	Type
AVO5-CLIP	Anti-vandal clips include 16pcs	Clips/Brackets
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS-BTN04/25	Batten Suspension Kits 2.5m length, 4 wires included	Suspension Kit
RMT-UNI	Universal Remote Control for Kosnic motion sensors	Remote Control

Rated Power (W)	Current (mA)	CCT (K)	Lumen (lm)
20	98	3000 (Warm White)	3300
20	98	4000 (Cool White)	3600
20	98	6000 (Day Light)	3500
26	120	3000 (Warm White)	4290
26	120	4000 (Cool White)	4420
26	120	6000 (Day Light)	4290
32	140	3000 (Warm White)	4640
32	140	4000 (Cool White)	5120
32	140	6000 (Day Light)	4960
36	160	3000 (Warm White)	5220
36	160	4000 (Cool White)	5760
36	160	6000 (Day Light)	5580



## AVOP4FT-SCT

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK