7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Avon Pro

Kosnic
LIGHTING • SIMPLY BETTER

08754 AVOP6FT-SCT

Avon Pro 6ft Twin 34W/44W/52W/60W switchable CCT

- High efficieny up to 170lm/W
- Optional plug-in microwave corridor sensor compatiable with Uni-Remote
- Switchable wattage and CCT (3000/4000/6000K)
- Optional plug-in emergency modules, available in standard, self-test and DALI
- T8 non-corrosive LED replacement
- Opal diffuser
- 20mm Conduit entry
- IP65 and vandal resistant (IK08)
- Optional plug-in DALI conversion module



Overview

The Avon Pro LED non-corrosive battens utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications. The product range is completely customisable and has optional microwave sensor and emergency options and is both wattage and CCT switchable.

IP65

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Materials	Housing: Polycarbonate
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	179,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary	
Product Code	AVOP6FT-SCT
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	19.5A / 310µs
Settable Wattages	34W, 44W, 52W, 60W
Driver Code/Part number	BK-PYN060E-A0350AYV (BOKE)
Driver Maximum Power (W)	60.2 W
Driver Output Current (mA)	200/ 250/ 300/ 350
Power Factor	0.90
Driver Power Factor	0.9
Settable Colour Temperatures	3000K, 4000K, 6000K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<2%
Lumens Output Maximum	9,600 lm
Emergency Luminous Flux	350 lm
L70B50 Lifetime (h) @Ta 25 °C	287,000 h
L80B10 Lifetime (h) @Ta 25 °C	179,000 h
L90B10 Lifetime (h) @Ta 25 °C	83,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	850
Blue Light Hazard	RG1
Weight	2.6Kg
Dimensions (L x W x D) (mm)	1865x117x80
Conduit Entry 20mm	Yes
LS Energy Efficiency Class	C

Tel: 01635 523 713
Email: sales@kosnic.com
Kosnic.com
Kosnic Lighting KosnicUK KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Avon Pro

Kosnic
LIGHTING • SIMPLY BETTER

08754 AVOP6FT-SCT


Optional Gear

Product Code	Description	Type
BEM303	BEM Emergency Module 3W for Kosnic Battens	Emergency Module
BEM303/SST	BEM Duo 3W Manual/Self test emergency module for Kosnic battens	Emergency Module
BEM303/DA	BEM 3W DALI switchable for Kosnic Battens	Emergency Module
SOV-M/D	Sova Plug-in microwave motion and daylight sensor	Microwave Sensor

Accessories

Product Code	Description	Type
AVO5-CLIP	Anti-vandal clips include 16pcs	Clips/Brackets
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS-BTN04/25	Batten Suspension Kits 2.5m length, 4 wires included	Suspension Kit
RMT-UNI	Universal Remote Control for Kosnic motion sensors	Remote Control

Rated Power (W)	Current (mA)	CCT (K)	Lumen (lm)
34	160	3000 (Warm White)	5270
34	160	4000 (Cool White)	5780
34	160	6000 (Day Light)	5610
44	190	3000 (Warm White)	6820
44	190	4000 (Cool White)	7480
44	190	6000 (Day Light)	7260
52	225	3000 (Warm White)	8060
52	225	4000 (Cool White)	8840
52	225	6000 (Day Light)	8580
60	260	3000 (Warm White)	8700
60	260	4000 (Cool White)	9600
60	260	6000 (Day Light)	9300



AVOP6FT-SCT

Overview

The Avon Pro LED non-corrosive battens utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications. The product range is completely customisable and has optional microwave sensor and emergency options and is both wattage and CCT switchable.

IP65

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Materials	Housing: Polycarbonate
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK