

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Avon Power



08755 AVOPW5FT-W40

Avon Power 65W/75W/85W/95W non-corrosive 5ft linear 4000K

- High efficiency up to 200lm/W
- Optional plug-in ON/OFF sensor compatible with Uni-Remote
- Switchable wattage
- Optional plug-in emergency modules, available in standard, self-test and DALI
- T8 non-corrosive LED replacement
- Opal diffuser
- 20mm Conduit entry
- IP65 and vandal resistant (IK08)



Overview

The Kosnic Avon Power LED non-corrosive batten utilises high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.



IP66



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP66
Materials	Housing: Polycarbonate
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	102,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	AVOPW5FT-W40
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	58A/156µs
Settable Wattages	65W, 75W, 85W, 95W
Driver Code/Part number	Xitanium 100W 350-500mA 200V DS 230V (Philips)
Driver Maximum Power (W)	104 W
Driver Output Current (mA)	350 / 400 / 450 / 500
Power Factor	0.9
Driver Power Factor	>0.9
Default CCT	4,000 K
SDCM of CCT	<3
CRI	82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	19,000 lm
Emergency Luminous Flux	320 lm
L70B50 Lifetime (h) @Ta 25 °C	155,000 h
L80B10 Lifetime (h) @Ta 25 °C	102,000 h
L90B10 Lifetime (h) @Ta 25 °C	55,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	850
Blue Light Hazard	RG1
Weight	2.2Kg
Dimensions (L x W x D) (mm)	1565x117x80
LS Energy Efficiency Class	B

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Avon Power



08755 AVOPW5FT-W40

Optional Gear

Product Code	Description	Type
BEM303	BEM Emergency Module 3W for Kosnic Battens	Emergency Module
BEM303/SST	BEM Duo 3W Manual/Self test emergency module for Kosnic battens	Emergency Module
BEM303/DA	BEM 3W DALI switchable for Kosnic Battens	Emergency Module
HON-M	Hontza Plug in microwave motion & daylight sensor	Microwave Sensor

Accessories

Product Code	Description	Type
AVO5-CLIP	Anti-vandal clips include 16pcs	Clips/Brackets
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS-BTN04/25	Batten Suspension Kits 2.5m length, 4 wires included	Suspension Kit
RMT-UNI	Universal Remote Control for Kosnic motion sensors	Remote Control

Rated Power (W)	Current (mA)	Lumen (lm)
65	300	13000
75	340	15000
85	390	17000
95	440	19000


Overview

The Kosnic Avon Power LED non-corrosive batten utilises high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP66
Materials	Housing: Polycarbonate
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK