

**5** 5 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

Nitro

Kosnic

08823 NTR03-BLK

## Nitro Emergency Downlight 3W Manual test Black

- Standard and corridor version with different lens
- Available in various finishes
- Non-maintained Downlight, >3hrs



### Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



### General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II

### Compliance

LVD	EN 60598-1:2024, EN 60598-2-22:2022, EN 60669-1:2018, EN 61347-2-7:2012+A1:2021, EN 61347-2-13:2014+A1:2017, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE, REACH

### Technical Summary

Product Code	NTR03-BLK
Lumens Output Maximum	130 lm
Maximum Efficiency	100 lm/W
Emergency Luminous Flux	130 lm
Maintained Luminous Flux	130 lm
Weight	0.10Kg
Dimensions (L x W x D) (mm)	33xØ70
Cut-Out (mm)	Ø50mm
UEM/EME Battery Life	5 y
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 45°C
UEM/EME Power Factor	0.4
Emergency Modes	Non-maintained Only
UEM/EME Test Function	Manual
UEM/EME CCT	6,000 K
UEM/EME Input Power (Max)	3 W
UEM/EME Protection	Class II
UEM/EME Dimensions (L x W x D) (mm)	28 x 70 ø (mounting recessed 50mm cut-out)
UEM/EME Emergency Operation Test	Manual
Beam Angle - Lumi (°)	45 Standard beam 25 Transverse/120 Axial Corridor beam

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK

**5** 5 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

# Nitro



08823 NTR03-BLK

## Accessories

Product Code	Description	Type
KBAT2000LFP1	LPF battery standard DD EME, NEKA, Trent OnSite 2ft	Battery


## Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



## General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK