

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Mesa

08935 MES2W20-SSCT-BLK

Mesa track spotlight 20W, 2-Wire, 1-Circuit, CCT switchable, Black

- Switchable CCT (3000/4000/5000K)
- Available with single circuit track adapter
- Two versions available for compatibility with either 2 wire or 3 wire single circuit track
- Available in white and black finishing



Overview

The Mesa LED track spotlight is suitable for both 2-wire and 3-wire single circuit tracks. It is CCT switchable and you can choose between the three available settings. The rotating and tilting spotlights are ideal for retail, showrooms, galleries and museums, delivering efficient light where it's needed.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK03
IP Rating	IP20
Materials	Housing: Die-cast aluminium
Protection Rating	Class I
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	54,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-2:2012, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	MES2W20-SSCT-BLK
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	18A/227.7µS
Default Power	20 W
Power Factor	0.95
Settable Colour Temperatures	3000K, 4000K, 5000K
SDCM of CCT	<6
CRI	90
Dimmable	N
Flicker	<1%
Lumens Output Maximum	1,700 lm
L70B50 Lifetime (h) @Ta 25 °C	86,000 h
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
L90B10 Lifetime (h) @Ta 25 °C	25,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.64Kg
Dimensions (L x W x D) (mm)	248xØ68
Beam Angle - Lumi (°)	38
LS Energy Efficiency Class	E

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only


Mesa



08935 MES2W20-SSCT-BLK

Overview

The Mesa LED track spotlight is suitable for both 2-wire and 3-wire single circuit tracks. It is CCT switchable and you can choose between the three available settings. The rotating and tilting spotlights are ideal for retail, showrooms, galleries and museums, delivering efficient light where it's needed.



MES2W20-SSCT-WHT/BLK

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK03
IP Rating	IP20
Materials	Housing: Die-cast aluminium
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

