

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Alcor

08944 ALC25C1-15D/BLK

Alcor Track Downlight 25W 15° Black CCT switchable 1 circuit

- CCT switchable 3000K/4000K/5000K
- Surface-mount options
- Available with 3 circuit and single circuit track adapter
- Available in black and white

Overview

The Kosnic LED Retail Downlights offer a versatile energy efficient LED lighting, where a high quality, high efficiency lighting solution is required.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK01
IP Rating	IP20
Protection Rating	Class I
Installation Area	Internal
L80B10 Lifetime (h) @Ta 25 °C	50,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	UKCA, CE, RoHS, WEEE

Technical Summary

Product Code	ALC25C1-15D/BLK
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	30A/150µs
Default Power	25 W
Power Factor	>0.94
Settable Colour Temperatures	3000K, 4000K, 5400K
SDCM of CCT	<6
CRI	≥82
Dimmable	N
Flicker	<5%
Lumens Output Maximum	2,000 lm
Maximum Efficiency	80 lm/W
L70B50 Lifetime (h) @Ta 25 °C	50,000 h
L80B10 Lifetime (h) @Ta 25 °C	50,000 h
L90B10 Lifetime (h) @Ta 25 °C	50,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.75Kg
Dimensions (L x W x D) (mm)	200xØ79
Beam Angle - Lumi (°)	15

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



Kosnic Lighting KosnicUK

KosnicLightingUK

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Alcor

Kosnic 

08944 ALC25C1-15D/BLK

Overview

The Kosnic LED Retail Downlights offer a versatile energy efficient LED lighting, where a high quality, high efficiency lighting solution is required.

Settable (Default in Bold)		Variable					
CCT (K)	Rated Power (W)	Total Luminous Flux (lm)	LS Energy Efficiency Class	LS Useful Luminous Flux (lm)	LS Chromaticity Co-Ordinates (X)	LS Chromaticity Co-Ordinates (Y)	LS R9 (LED/O)
3000	25	1700	F	2400	0.436	0.406	6
4000	25	2000	E	2900	0.382	0.378	16
5400	25	1900	E	2690	0.335	0.353	5




IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK01
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal



ALC25C1

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

