7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Onyx 2 in 1

Kosnic
LIGHTING • SIMPLY BETTER

08973 ONY05/SST

Onyx Duo 5W manual&Self- test non-maintained high bay EME

- Select manual or self-test mode via the internal dual-mode DIP switch
- To adjust green LED indicator brightness, press and hold the test button for more than 3 seconds
- To set the duration test interval, press the button on the remote twice
- Automatic Self-test conforming to BS-EN-62034
- Non-Maintained, 3hrs
- Easy to install on LED high bay with eyebolt
- Push-wire loop-in and loop-out terminal block included
- Built-in green status indicator





Overview

The Onyx add-on emergency light for LED high bay luminaires available in 2 in 1 standard & self-test or DALI versions is suitable for installation on high bays with an eyebolt. It provides an emergency operation time of three hours giving you complete peace of mind in your lighting design.

IP65

General Information

IP Rating	IP65
Materials	Housing: Polycarbonate + Powder coated stainless steel
Installation Area	Internal and External
UEM/EME Protection	Class II

Compliance

Others	UKCA, CE, RoHS, WEEE, REACH

Technical Summary	
Product Code	ONY05/SST
Lumens Output Maximum	600 lm
Emergency Luminous Flux	600 lm
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 50°C
UEM/EME CCT	5,000 K
UEM/EME Input Power (Max)	4 W
UEM/EME Protection	Class II
UEM/EME Weight	1 kg
UEM/EME Dimensions (L x W x D) (mm)	406x110x30 (293xx70x62) see line drawing
Beam Angle - Lumi (°)	45

Tel: 01635 523 713
Email: sales@kosnic.com
Kosnic.com
Kosnic Lighting KosnicUK KosnicLightingUK

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Onyx 2 in 1

Kosnic
LIGHTING • SIMPLY BETTER

08973 ONY05/SST


Accessories

Product Code	Description	Type
BATS40LFP2	Battery LiFePO4, 4000mAh capacity, 6.4V Voltage	Battery

Overview


The Onyx add-on emergency light for LED high bay luminaires available in 2 in 1 standard & self-test or DALI versions is suitable for installation on high bays with an eyebolt. It provides an emergency operation time of three hours giving you complete peace of mind in your lighting design.

IP65



General Information

IP Rating	IP65
Materials	Housing: Polycarbonate + Powder coated stainless steel
Installation Area	Internal and External
UEM/EME Protection	Class II



Tel: 01635 523 713
Email: sales@kosnic.com
Kosnic.com
Kosnic Lighting KosnicUK KosnicLightingUK KosnicUK