

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only



# Nitro 2 in 1

09047 NTR05/SST

## Nitro Duo Emergency Downlight 3W Manual & Self-test White

- Select manual or self-test mode via the internal dual-mode DIP switch
- Automatic Self-test conforming to BS-EN-62034
- To adjust green LED indicator brightness, press and hold the test button for more than 2 seconds
- Non-maintained Downlight, 3hrs



### Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



### General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II
L80B10 Lifetime (h) @Ta 25 °C	77,000 h

### Compliance

Others UKCA, CE, RoHS, WEEE, REACH

### Technical Summary

Product Code	NTR05/SST
Lumens Output Maximum	300 lm
Emergency Luminous Flux	300 lm
L80B10 Lifetime (h) @ Ta 25 °C	77,000 h
Weight	0.1Kg
Cut-Out (mm)	Ø58mm
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 50°C
Emergency Modes	Maintained or Non-maintained
UEM/EME CCT	6,000 K
UEM/EME Input Power (Max)	5 W
UEM/EME Protection	Class II
UEM/EME Weight	0.1 kg
UEM/EME Dimensions (L x W x D) (mm)	34xØ70
UEM/EME Emergency Operation Test	Automatic and Manual
Beam Angle - Lumi (°)	45

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)



Kosnic Lighting KosnicUK KosnicLightingUK

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

# Nitro 2 in 1

09047 NTR05/SST

## Accessories

Product Code	Description	Type
BATS18LFP2/L	Battery LiFePO4, 3600mAh capacity, 3.2V	Battery

## Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



## General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com






**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only

# Nitro 2 in 1

09047 NTR05/SST

## Push switch

 x1	FUNCTIONAL TEST
 x3	DURATION TEST
 HOLD	INDICATOR DIMMING

## Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



## General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

