

Nyos

09080 NYO8IN18-W40

Nyos, circular panel downlight, 8 inch, 18W, 4000K

- IP20 when ceiling recess mounted
- Flicker free
- Ultra-slim profile
- Optional DALI, 1-10V (0-10V) driver



Overview

The Nyos circular LED Panel is an easy-to-retrofit replacement for downlights. These advanced panels are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light. The Edge-Lit technology provides constant light across its surface.



General Information

| | |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 50°C |
| IK Rating | IK04 |
| IP Rating | IP44 |
| Protection Rating | Class III |
| Installation Area | Internal |
| L80B10 Lifetime (h) @Ta 25 °C | 50,000 h |

Compliance

| | |
|--------|---|
| LVD | EN 60598-1:2024, EN 60598-2-2:2012 |
| EMC | EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023 |
| Others | UKCA, CE, RoHS, WEEE |

Technical Summary

| | |
|------------------------------------|--------------------|
| Product Code | NYO8IN18-W40 |
| Input Voltage Supply | 220-240Vac 50/60Hz |
| Inrush Current (peak/duration) (A) | 20.5A/90µs |
| Default Power | 18 W |
| Driver Code/Part number | CYC017SNL030N |
| Driver Maximum Power (W) | 17 |
| Driver Output Current (mA) | 300 |
| Power Factor | 0.96 |
| Driver Power Factor | 0.9 |
| Default CCT | 4,000 K |
| SDCM of CCT | <6 |
| CRI | ≥82 |
| Dimmable | N |
| Flicker | <2% |
| Lumens Output Maximum | 1,700 lm |
| Maximum Efficiency | 95 lm/W |
| Emergency Luminous Flux | 250 lm |
| L70B50 Lifetime (h) @Ta 25 °C | 50,000 h |
| L80B10 Lifetime (h) @Ta 25 °C | 50,000 h |
| L90B10 Lifetime (h) @Ta 25 °C | 32,000 h |
| Nominal Lifetime (h) | 50,000 h |
| Glow wire temperature(°C) | 650 |
| Blue Light Hazard | RG1 |
| Weight | 0.56Kg |
| Dimensions (L x W x D) (mm) | 28xØ240 |
| Cut-Out (mm) | Ø222mm |
| LS Energy Efficiency Class | E |

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com



09080 NYO8IN18-W40

Optional Gear

| Product Code | Description | Type |
|----------------|---|----------------------------|
| UEM03/ST | Universal Emergency Module 3W Self Test | Self-test Emergency Module |
| UEM03 | Universal Emergency Module 3W | Emergency Module |
| CYC030TDC30-90 | 30W DALI2 1-10V primary push dim driver (KL30C-PDiIV) | Dimmable Driver |
| DRC30/DA | Dimmable Driver: 30W DALI, 1-10V, Primary PUSH Driver | Dimmable Driver |
| EMPAD01 | Neka Emergency Downlight kit 2.5W Manual test | Emergency Module |
| EMPAD01/ST | Neka Emergency Downlight kit 3.5W Self-test | Self-test Emergency Module |


Overview

The Nyos circular LED Panel is an easy-to-retrofit replacement for downlights. These advanced panels are suitable for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light. The Edge-Lit technology provides constant light across its surface.




General Information

| | |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -20°C to 50°C |
| IK Rating | IK04 |
| IP Rating | IP44 |
| Nominal Lifetime (h) | 50,000 h |
| Protection Rating | Class III |
| Installation Area | Internal |



NYO8IN18



Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

